Pager4 PRO

Available on the App Store

GET IT ON Google Play

Contact controlled communicator, which can be used as an optional reporting device for alarm control panels, as a standalone GSM reporting device, or as a 4/6-zone alarm control device with arming and disarming option.

MOBILE APPLICATION

TELL CONTROL CENTER

Pager4 – 3G.IN4.R2*	Pager4 – 3G.IN6.R1*	Pager4 PRO – 2G.IN4.R2	Pager4 PRO – 2G.IN6.R1	Pager4 PRO – 3G.IN4.R2*	Pager4 PRO – 3G.IN6.R1*
3G / 2G / GSM	3G / 2G / GSM	2G / GSM	2G / GSM	3G / 2G / GSM	3G / 2G / GSM
900/2100 MHz @UMTS, 900/1800 @GSM/GPRS	900/2100 MHz @UMTS, 900/1800 @GSM/GPRS	850/900/1800/1900 MHz @GSM/GPRS	850/900/1800/1900 MHz @GSM/GPRS	900/2100 MHz @UMTS, 900/1800 @GSM/GPRS	900/2100 MHz @UMTS, 900/1800 @GSM/GPRS
-20 °C – +70 °C	-20 °C – +70 °C	-20 °C – +70 °C	-20 °C – +70 °C	-20 °C – +70 °C	-20 °C – +70 °C
12-30 VAC/DC	12-30 VAC/DC	12-30 VAC/DC	12-30 VAC/DC	12-30 VAC/DC	12-30 VAC/DC
500 mA @ 12 VDC	500 mA @ 12 VDC	500 mA @ 12 VDC	500 mA @ 12 VDC	500 mA @ 12 VDC	500 mA @ 12 VDC
120 mA @ 12 VDC	120 mA @ 12 VDC	120 mA @ 12 VDC	120 mA @ 12 VDC	120 mA @ 12 VDC	120 mA @ 12 VDC
Plastic	Plastic	Plastic	Plastic	Plastic	Plastic
Connectable	Connectable	Connectable	Connectable	Connectable	Connectable
84x72x32 mm	84x72x32 mm	84x72x32 mm	84x72x32 mm	84x72x32 mm	84x72x32 mm
200 g	200 g	200 g	200 g	200 g	200 g
4	6	4	6	4	6
4	6	4	6	4	6
✓	✓	✓	✓	✓	✓
2	1	2	1	2	1
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
–	–	✓	✓	✓	✓
–	–	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
USB / IP	USB / IP	USB / IP	USB / IP	USB / IP	USB / IP
✓	✓	✓	✓	✓	✓
1	1	1	1	1	1
10	10	10	10	10	10
10	10	10	10	10	10
4	4	4	4	4	4
2	2	2	2	2	2
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
Yes / 1000	Yes / 1000	Yes / 1000	Yes / 1000	Yes / 1000	Yes / 1000
✓	✓	✓	✓	✓	✓
–	–	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓