

## UNii I/O module (excl. PSU)



### FEATURES AND BENEFITS

- + Quick and easy installation
- + 8 inputs standard, expandable to 16 zones
- + 4-open collector (OC) outputs 200 mA
- + Delivered in a small metal housing without power supply
- + Built-in buzzer for location determination
- + Grade 2 certified

With the UNii I/O (excl. PSU) module for the UNii alarm system it is possible to expand the system with extra hardwired zones. The UNii I/O module is also available in a version including power supply also with the option to expand outputs.

### Characteristics

The UNii I/O module (excl. PSU) in a compact metal cabinet does not include power and must be powered via the RS-485 bus. This module has eight hardwired zones and two outputs (two open collector outputs, max. 200 mA).

The UNii I/O module (excl. PSU) can be expanded with an 8-input expansion board (max. 1) to be able to connect a total of 16 zones in the cabinet. The UNii I/O module (excl. PSU) cannot be expanded with extra outputs.

## Specifications

Supply voltage:	via RS-485 bus
Current drain:	60 mA
Inputs:	8
Outputs:	4 (open collector 200mA)
Operating temperature:	0 ° to +50 ° C
Dimensions:	177 x 155 x 35 mm (LxWxH)
Color:	White
Weight:	2090 g
Certification:	EN50131 approved (Grade 2) NCP registered

## Order Information

ART.NR.	DESCRIPTION
004600	UNii control panel 32 inputs
004602	UNii control panel 128 inputs
004604	UNii control panel 512 inputs
004662	UNii I/O module (excl. PSU) in cabinet
004664	UNii 8 inputs expansion board
004682	UNii Expander mount kit

